

WARNING: KEEP OUT OF REACH OF CHILDREN

ERASE[®] ANTIFOAM

NOT FOR RESALE

For use with ERASE Jetting Liquid

Read entire label before use.

Erase Antifoam is an aqueous emulsion of polydimethylsiloxane fluid for use as an antifoam agent. It is a free-flowing, ready to use liquid that may be added before or after foaming occurs. The amount required varies but will usually be 10 - 100mL/100L of water. It is recommended to start with the 10mL/100L rate and increase only as necessary.

DIRECTIONS FOR USE:

1. Add water to the tank.
2. Add ERASE Antifoam directly to the tank.
3. Add ERASE Jetting Liquid (refer to product label for quantity).

Further advice on reduction of foaming:

- Avoid excessive mixing or recirculation.
- Do not use excessive pressure at the spray nozzles - 450 kPa [65psi] is recommended.
- Volume rather than pressure is important therefore ensure the spray race has large diameter nozzles (i.e. 4 to 5mm).

STORAGE:

Store in a cool dry place in original container.

Approved pursuant to the HSN0 Act 1996, No: HSR002503.

HANDLING PRECAUTIONS

Warning - May cause eye irritation, avoid contact with eyes.

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. If eye irritation persists, get medical advice.

ENVIRONMENTAL PROTECTION

Very toxic to terrestrial invertebrates. Harmful to the soil environment. Avoid release to the environment and avoid contamination of any water supply with product or empty container.

DISPOSAL

Dispose of any unused contents in an approved landfill. Triple rinse empty container. Recycle or crush empty container and bury in a suitable landfill.

EMERGENCY RESPONSE

For specialist advice in an emergency call, 0800 CHEMCALL (0800 243 622)

See Safety Data Sheet for further information, www.intervet.com

Batch:

DoM:

Net Contents: 1 litre

 **Intervet**
Schering-Plough Animal Health

